



Description

GZMI-1000-2F4R1C is an hardened 6-port Industrial Ethernet Switch, provides non-blocking wire-speed performance in harsh industrial environment.

It provides 4-port 10/100/1000BASE-TX RJ45 +2G SFP delivered in an IP40 rugged, strong case with redundant power system. Its slim case is suitable for such applications as surveillance system deployments, control management and wireless service in climatically demanding environments with wide temperature range from -40°C to 80°C.

GZMI-1000-2F4R1C provides the flexibility to all kinds of 10//100/1000Mbps Ethernet Media on RJ-45 port and performs highly stable fiber performance.

GZMI-1000-2F4R1C is packaged in a compact IP40 case that allows either DIN rail or panel mounting to have efficient usage of cabinet space. It provides an integrated power supply with a wide range of voltages for worldwide operation. It also offers dual-redundant, reversible polarity 12V DC to 52V DC power supply inputs for high availability applications requiring dual or backup power inputs.

Features

- ❖ Data control: support 802.3x full duplex flow control, support network storm suppression
- ❖ Redundant network: support STP/RSTP/MSTP, support ERPS (self-healing time <20ms)
- ❖ Support IPv6, static routing
- ❖ Support DHCP Server, DHCP replay, Qos , IGMP Snooping
- ❖ Support port-based VLAN Port, IEEE 802.1Q VLAN and GVRP protocol, simple network planning
- ❖ QoS: Support QoS (IEEE 802.1p/1Q) and TOS/ Diffserv to increase network stability
- ❖ Security management: support ACL access control list, support 802.1x, support user classification management
- ❖ Management function: support Web, SNMP management mode
- ❖ Monitoring maintenance: support port mirroring, interface status monitoring, log management
- ❖ Support 1588 clock protocol

Specification

Model No.	GZMI-1000-2F4R1C
-----------	------------------

Shenzhen GZCOM Communication Co., Ltd.

Email: sales@gzcomm.com
<https://www.gzcomm.com>

1000Base-TX Port	4 port RJ-45 auto-MDI / MDI-X
1000Base-FX Port	2G SFP Slot
Performance Specification	Bandwidth (switch capacity): 38Gbps Packet Buffer Memory: 12Mbit Packet Forwarding Rate: 28.3Mpps MAC Address Table: 8K
Installation	DIN rail
Maximum Frame Size	10240bytes
Flow Control	Back pressure for half duplex, IEEE 802.3x pause frame for full duplex
Enclosure	IP40 slim type metal case
LED Indicator	Power: Red Fiber: Link 2(Green) Ethernet: Yellow
Power Input	12 to 52V DC redundant power
Power Consumption	3 watts
Surge Protection	$\pm 4KV$
Network Protocols	IEEE802.3 10BASE-T; IEEE802.3i 10Base-T; IEEE802.3u;100Base-TX/FX; IEEE802.3ab 1000Base-T; IEEE802.3z 1000Base-X; IEEE802.3x;
Network cables	10BASE-T: Cat3,4,5 UTP(≤ 100 meter) 100BASE-TX: Cat5 or later UTP(≤ 10 meter) 1000BASE-TX: Cat6 or later UTP(≤ 100 meter)
	FCC CFR47 Part 15,EN55022/CISPR22, Class A IEC61000-4-2 (ESD): $\pm 8kV$ (contact), $\pm 12kV$ (air)

Shenzhen GZCOM Communication Co., Ltd.

Email: sales@gzcomm.com
<https://www.gzcomm.com>

Industry Standard	<p>IEC61000-4-3 (RS): 10V/m (80~1000MHz)</p> <p>IEC61000-4-4 (EFT): Power Port: $\pm 4\text{kV}$; Data Port: $\pm 2\text{kV}$</p> <p>IEC61000-4-5 (Surge): Power Port: $\pm 2\text{kV/DM}$, $\pm 4\text{kV/CM}$; Data Port: $\pm 2\text{kV}$</p> <p>IEC61000-4-6 (CS): 3V (10kHz-150kHz); 10V (150kHz-80MHz)</p> <p>IEC61000-4-16 (Common mode conduction): 30V (cont.), 300V (1s)</p>
Certificate	CE FCC Rohs compliance
MTBF	>300,000hours
Dimensions (W x D x H)	143.7 x 103 x 44.2 mm
Weight	<p>Product Weight: 0.36KG</p> <p>Packing Weight: 0.46KG</p>
Working Environment	<p>Working temperature: $-40\sim 85^{\circ}\text{C}$;</p> <p>Storage temperature: $-40\sim 85^{\circ}\text{C}$</p> <p>Relative Humidity: 5%~95 % (no condensation)</p>
Warranty	1-year replacement with new item; 3-years for main parts.

Management Features

Interface	<p>IEEE802.3X (Full-duplex), Port temperature protection setting</p> <p>Port green Ethernet Energy-saving setting Broadcast storm control based</p> <p>on port speed. The speed limit of the message flow in the access port.</p> <p>The minimum particle size is 64Kbps.</p>
Layer 3 Features	<p>L2+ network management, IPV4/IPV6 management L3 soft routing forwarding,</p> <p>Static route, Default route @ 128 pcs, APR@1024pcs</p>


Shenzhen GZCOM Communication Co., Ltd.

Email: sales@gzcomm.com
<https://www.gzcomm.com>

VLAN	4K VLAN based on port, IEEE802.1q VLAN based on the protocol VLAN based on MAC Voice VLAN, QinQ configuration Port configuration of Access, Trunk, Hybrid
Port Aggregation	LACP, Static aggregation Max 8 aggregation groups and 8 ports per group.
Spanning Tree	STP (IEEE802.1d), RSTP (IEEE802.1w), MSTP (IEEE802.1s)
Industrial Ring Network Protocol	G.8032 (ERPS), Recovery time less than 20ms 250 Ring at most, Max 250 devices per ring. Multicast
Multicast	MLD Snooping v1/v2, Multicast VLAN IGMP Snooping v1/v2, Max 1024 multicast groups, Fast log out
Port Mirroring	Bidirectional data mirroring based on port
QoS	Flow-based Rate Limiting Flow-based Packet Filtering 8*Output queues of each port 802.1p/DSCP priority mapping Diff-Serv QoS, Priority Mark/Remark Queue Scheduling Algorithm (SP, WRR, SP+WRR)
ACL	Port-based Issuing ACL, ACL based on port and VLAN L2 to L4 packet filtering, matching first 80bytes message. Provide ACL based on MAC, Destination MAC address, IP Source, Destination IP, IP Protocol Type, TCP/UDP Port, TCP/UDP Port Range, and VLAN, etc.
Security	IP-MAC-VLAN-Port binding ARP inspection, Anti-DoS attack AAA & RADIUS, MAC learning limit Mac black holes, IP source protection IEEE802.1X & MAC address authentication Broadcast storm control, Backup for host datum SSH 2.0, SSL, Port isolation, ARP message speed limit User hierarchical management and password protection

DHCP	DHCP Client, DHCP Snooping, DHCP Server, DHCP Relay
Management	<p>One-key recovery Cable Diagnose, LLDP</p> <p>Web Management (HTTPS) NTP, System work log, Ping Test CPU</p> <p>instant utilization status view</p> <p>Console/AUX Modem/Telnet/SSH2.0 CLI</p> <p>Download & Management on FTP, TFTP, X modem, SFTP, SNMP V1/V2C/V3</p>
System	<p>Category 5 Ethernet network cable</p> <p>Web browser: Mozilla Firefox 2.5 or higher, Google browser chrome</p> <p>V42 or higher, Microsoft Internet Explorer10 or later;</p> <p>TCP/IP, network adapter, and network operating system (such as Microsoft Windows, Linux, or Mac OS X) installed on each computer in a network</p>

Dimensions



GZCOM reserves the right to make changes to the products or information contained herein without notice. No liability is assumed as a result of their use or application. No rights under any patent accompany the sale of any such products or information.

Published by Shenzhen GZ Communication Co., Ltd.

Copyright ©GZCOM

All Rights Reserved

Shenzhen GZCOM Communication Co., Ltd.

Email: sales@gzcomm.com
<https://www.gzcomm.com>